


FOR A GREEN WORLD

HELIXDRIVE The Eccentric Screw Pumps for media with low and high viscosity

HELIXDRIVE

The Eccentric Screw Pumps with exceptional performance



Unique rotor

The low friction hollow rotor – the key component of every eccentric screw pump – is manufactured in a unique special process in the BAUER factory and is absolutely break-proof.

Longer durability

Tough tool steel and a consistent wall thickness of 8 mm prevent heat accumulation and stress cracks. The special coating applied makes for a tough and smooth surface.

This process also ensures a longer life of the stator rubber, as the smooth rotor surface causes considerably less abrasion.

Exceptional smoothness

The light weight of the low friction hollow rotor guarantees consistent running smoothness in all speed ranges.







For media with low and high viscosity:

- Thick slurry
- Liquid manure
- Sewage sludge
- Bog
- Spent grains
- Draff
- Molasses
- Potato pulp
- Starch etc.



Eccentric screw pump with motor drive – ideal for stationary use in both agricultural and industrial applications.

Use:

- intertank transfer
- dosing
- feeding
- flushing
- bringing in

Characteristics:

- Abrasion resistant, hardened smooth-running cupped rotors made of tough toolsteel – manufactured by BAUER with a special technology and absolutely break-proof
- thermally optimated bearing for continuous operation
- mechanical seal running in oil bath
- large dimensioned intake and pressure connections to reduce plugging
- access eye in intake housing
- robust, permanently lubricated cardan joints
- compact form of structure
- chassis for quick and safe mounting
- Iockable drive for easy change of rotor and stator
- quiet running
- easy to maintain
- self priming

HELIX Eccentric Screw Pumps



High quality and reliability

In House factory production guarantees both reliable and immediate availability of consistently high-quality spare parts.




Extensive accessories such as:

- Stone catcher in form of a box or can
- Aspiration mouth with integrated stone catcher
- Drum filling station with adjustable discharge pipe
- All components for suction and pressure lines

Technical Data


Pump type	HELIXDRIVE 553	HELIXDRIVE 556	HELIXDRIVE 753	HELIXDRIVE 756	HELIXDRIVE 1103	HELIXDRIVE 1106
Performance kW	5.5	5.5	7.5	7.5	11	11
Flow high max. m	30	60	30	60	30	60
Flow rate max. m ³ /h	38	15	48	18	65	35
Flange suction side DN	150	150	150	150	150	150
Flange pressure side DN	125	125	125	125	125	125
Dimensions mm A x B	1850 x 400	1745 x 400	1873 x 400	1850 x 400	1868 x 400	1950 x 400

Rated power with water





HELIXDRIVE Eccentric Screw Pumps are multifunctional



Your Dealer:



Calle 132 # 50 - 45 Tel: (+57)(1) 626 1955 · 626 2797 www.comercialderiegos.com info@comercialderiegos.com Bogotá, Colombia Röhren- und Pumpenwerk BAUER Ges.m.b.H. 8570 Voitsberg, Austria Tel. +43 3142 200-0 Fax +43 3142 200-320 / -340 sales@bauer-at.com www.bauer-at.com

A BAUER Group company

